

MATERIAL SAFETY DATA SHEETS:

BestLine International Research Inc.

Effective Date: April 30, 2008

Date Printed: May 13, 2008

MSDS: BestLine J904

1.

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT CODE: 26000

PRODUCT NAME: **BestLine Synthetic Power-Train Lubricant**

PRODUCT USE: Extreme Pressure Additive, Synthetic Lubricant, and Metal Treatment

BestLine International Research Inc. 2979 Barley Mill Road, Yorklyn, Delaware, 19736

TEL: 1-866-720-5140 FAX: (604) 534-4944 Emergency Call: CHEMTREC: (800) 424-9300

E-mail: rjsloancan@yahoo.ca

2.

COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL FAMILY: Blend of Synthetic Petroleum Products and Oxidation Inhibitors

PRODUCT GRADES: ISO 15

CAS REGISTRY NO: No: No

WHMIS CONTROLLED: No

PRODUCT USE: Automotive and Industrial Lubricant Additive

Hydrosomerized (Isodewaxed Group II +) HT Base Oils and Proprietary Additives (All Synthetic Ingredients) CAS 72623-86-0

Aliphatic Hydrocarbons CAS 8052-41-3

3.

HAZARDOUS INGREDIENTS

Component Volume %: CAS Number (8052-41-3) LD 50 LC 50

None

Oxidation Inhibitors and detergents: PEL 4 MG/M3 TLV 4MG/M3

Vacuum Distilled Aliphatic Solvents 100PPM

EMERGENCY OVERVIEW

Clear to light red translucent liquid. Avoid extreme temperatures.

HMIS Rating: HEALTH: 1 FLAMMABILITY: 1. REACTIVITY: 1. PPE: C

POTENTIAL HEALTH EFFECTS

EYE: May produce a mild transient irritation.

SKIN: May produce mild irritation, which is readily reversible. Not known to be a sensitizer. Not readily

absorbed through skin.

INGESTION: Not expected to produce toxic effect when ingested.

INHILATION: Under normal conditions, this product is nontoxic; however, under significant decomposition conditions, a mild to moderate irritation of the upper respiratory tract can occur due to the potential of a slight amount of hydrogen chloride gas.

CHRONIC EFFECTS: The toxicity profile would suggest a slight hazard to those chronically exposed to the product over a lengthy period of time. The liver is the probable target organ, should massive systemic poisoning occur. Treat as synthetic motor oil or mineral oil.

SIGNS AND SYMPTOMS: May produce mild, reversible eye and skin irritation.

4.

FIRST AID MEASURES

EYE: Immediately flush eyes with a direct stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: Wash contaminated area with soap and warm water, remove contaminated clothing. Do not use solvents for cleaning. If irritation occurs, seek medical attention.

INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of clean water. (If available, give several glasses of milk). If vomiting occurs spontaneously, keep airway clear and give more water. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: Under fire conditions, remove to fresh air. If breathing is difficult, have a trained person administer oxygen. If respiration stops, give mouth-to-mouth resuscitation. GET MEDICAL ATTENTION.

5.

FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: Flash Point Cleveland Open Cup <100° C (min)

FLAMMABLE LIMITS: Upper Flammable Limit: Flammable

Lower Flammable Limit: Flammable

This material will burn will not readily ignite.

FLAMMABLEILITY CLASSIFICATION: No data.

AUTOIGNITION TEMPERATURE: No data available.

HAZARDOUSCOMBUSTION PRODUCTS: Fumes, smoke, may form oxides of carbon and nitrogen.

EXTINGUISHING METHOD: Fires involving this product are unlikely, but should one occur, it could be controlled by carbon dioxide, dry chemical, foam or water fog. May form toxic material such as: carbon

dioxide, carbon monoxide, hydrogen chloride and various hydrocarbons

ADDITIONAL CONSIDERATIONS: OIL FLOATS ON WATER. Do not use direct or heavy water stream to fight fire. Use organic vapor respirator or self-contained breathing apparatus to fight fire.

SENSITIVITY TO IMPACT: None.

SENSITIVITY TO STATIC DISCHARGE: None. As a precaution, always ground larger metal containers before filling or discharging.

NFPA 704 RATING: HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 1 SPECIAL:

6.

ACCIDENTIAL RELEASE MEASURES

Wear protective equipment. Observe handling precautions. If material is spilled or released to the atmosphere, steps should be taken to contain liquids and prevent discharge to streams or sewer systems; and control or stop loss of volatile materials to the atmosphere. Contained materials should be cleaned up using a vacuum truck or absorbent material and remove to approved waste disposal area. Spills or releases should be reported, if required to the appropriate local, state and federal regulatory agencies.

7.

HANDLING AND STORAGE

HANDLING: Prevent possible static discharge when handling material. Do not wear contaminated clothing. Wash hands and face prior to eating, drinking, smoking, use of restrooms when leaving work. Do not dispose of material or empty container to the environment.

STORAGE: To prevent deterioration, with subsequent discoloration and possible decomposition with liberation oxides of carbon and nitrogen, store products in closed containers at temperatures not to exceed 66° C.

VENTILATION: No special ventilation required under normal use or blending procedures. Use local exhaust ventilation when the product is heated over 100 C: or mist, spray, dust or vapor may be generated.

SPECIAL PACKAGING MATERIAL: Not applicable.

8.

EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Washing or shower and eyewash facilities should be accessible.

EYE/FACE PROTECTION: Face shield and goggles should be worn where mist, spray, or dust may be generated when product is heated over 100° C.

SKIN PROTECTION: Impervious Viton gloves should be worn. Standard work clothing. Standard work shoes. Shoes that can't be decontaminated should be discarded. Wash contaminated clothing with soap and warm water and dry before reuse.

RESPIRATORY PROTECTION: Respiratory protection is not required under normal use. Use NIOSH/MSHA approved respiratory protection following manufacturer's recommendation where mist, spray, dust or vapor may be generated and where the product is heated substantially.

EXPOSURE GUIDELINES: (See Section 2.)

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Light red translucent liquid.

ODOR: Slight odor.

PHYSICAL STATE: Liquid.

PH: Not Applicable

VAPOR PRESSURE FOR COMPONENT: 33.00MM Hg @ 20° C.

VAPOR DENSITY: Air = 1. Heavier than Air.

BOILING POINT: Greater than 82° C. @ 760.00 mm Hg. Stable under normal conditions without.

MELTING POINT: Not Applicable

SPECIFIC GRAVITY: 1.09 @ 25° C.

SOLUBILITY IN WATER: Negligible.

EVAPORATION RATE: Negligible. Slower than ether.

FLASH POINT: Cleveland Open Cup <100° C.

PERCENT VOLATILES: Less than 25%

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Elevated temperatures and strong alkalies will promote the decomposition of the product. The thermal decomposition is a time/temperature relationship. At room temperature, decomposition is virtually nil.

CONDITIONS TO AVOID: Elevated temperatures for extended periods of time.

INCOMPATIBILITY: N/A

HAZARDOUS POLYMERIZATION: Not know to polymerize.

HAZARDOUS DECOMPOSITION: Incomplete combustion can produce carbon dioxide and or carbon monoxide.

11.

TOXICOLOGICAL INFORMATION

EYES EFFECT: No Data

SKIN EFFECT: No Data

INGESTION EFFECT: No Data

INHALATION DATA: No Data

SUBCHRONIC EFFECT: No Data

CHRONIC EFFECTS/CARCINOGENICITY: Not listed as a carcinogen- IRAC, NTP, and OSHA.

EPIDEMIOLOGY: No Data

TERATOLOGY: No Data

REPRODUCTIVE EFFECTS: No Data

NEUROTOXICITY: No Data

MUTAGENICITY: No Data

SYNERGISTIC PRODUCTS: No Data

12.

ECOLOGICAL INFORMATION

ECCOTOXICITY: No Data

ENVIROMENTAL FATE: No Data

PHYSICAL/CHEMICAL: Refer to sections 9 and 10.

13.

DISPOSAL CONSIDERATIONS

METHOD OF DISPOSAL: According to local, state, province and federal regulations.

Package, store, transport and dispose of all clean-up material and contaminated equipment in accordance with all applicable federal, state, province and local health authorities and environmental regulations. Shipments of waste material may be subject to manifesting requirements per applicable regulations. Appropriate disposal will depend on nature of the waste material and should be performed by competent and properly permitted contractors. Please Recycle. Used oil may be returned to any oil collection center for re-refining.

14.

TRANSPORTATION

DOT SHIPPING NAME: N/A

DOT HAZARD CLASS/DESCRIPTION: N/A

DOT LABEL: N/A

DOT PLACARD: N/A

DOT UN/NA NUMBER: N/A

DOT PRODUCT RQ: N/A

IMO CLASSIFICATION: N/A

EEC CLASSIFICATION: N/A

EEC LABEL: N/A

EEC R: N/A

EEC S: N/A

TRANSPORT CANADA PIN: N/A

*N/A = Not Applicable

15.

REGULATORY INFORMATION (Not meant to be all inclusive)

U.S FEDERAL REGULATIONS

TSCA: Not shown in inventory.

OSHA: Non

CERCLA SARA HAZARD CATEGORY: SECTION 311 AND 312: This product has been reviewed according to the EPA "Hazard Category" promulgated under sections 311 and 312 of the Superfund Amendment and reauthorization Act of 1986 (SARA Title III) and is considered, under the application definitions, to meet the following categories: None

Section 313; This product contains the following substance subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372: None

NOS-UN-1993 (173.115)

INTERNATIONAL REGULATIONS

Canadian WHIMIS: None

Canadian Environmental Protection Act (CEPA): Appears in the Domestic Substances List
EINECS: No specific listing in inventory.

State Regulations: No specific listings in inventory.

16.

OTHER INFORMATION

MSDS Status: Issued April 30, 2008

The information herein is given in good faith, but no warranty, expressed or implied, is made. Consult BestLine International Research Inc.

MATERIAL SAFETY DATA SHEET